

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
2.40"	ITLT0240QVCF25UM Integrated 4 Wire RTP	TTL	QVGA 240x320 3:4 Normally White, Transmissive	420	18 Bit	80/80/70/80	12 O'Clock	-20~70 -30~80	42.70 x 59.45 x 3.98 36.72 x 48.96
2.40"	ITLT0240QVCN23UM	TTL	QVGA 240x320 3:4 Normally White, Transmissive	500	18 Bit	80/80/70/80	12 O'Clock	-20~70 -30~80	42.70 x 59.45 x 3.00 36.72 x 48.96
3.00"	ITLT0300UNCN12WM	TTL	WQVGA 240 x 400 Normally White, Transmissive	300	18 Bit	70/70/55/70	12 O'Clock	-20~70 -30~80	45.04 x 77.00 x 2.75 38.88 x 64.80
3.50"	ITLT0350QVRF37KL Integrated 4 Wire RTP	TTL	QVGA 240x320 3:4 Normally White, Transmissive	230	18 Bit	55/55/60/55	6 O'Clock	-20~70 -30~80	63.00 x 85.00 x 4.30 53.28 x 71.04
3.50"	ITLT0350QVRN33KL	TTL	QVGA 240x320 3:4 Normally White, Transmissive	230	18 Bit	55/55/60/55	6 O'Clock	-20~70 -30~80	63.00 x 85.00 x 3.10 53.28 x 71.04
3.50"	ITLT0350QVRF12CM Integrated 4 Wire RTP	TTL	QVGA 320x240 4:3 Normally White, Transmissive	250	24 Bit	60/60/50/55	6 O'Clock	-20~60 -30~70	76.90 x 63.90 x 3.26 90.08 x 52.56
3.50"	ITLT0350QVRT03CM Integrated 4 Wire RTP	TTL	QVGA 320x240 4:3 Normally White, Transmissive	250	24 Bit	60/60/50/55	6 O'Clock	-20~70 -30~80	76.90 x 63.90 x 3.26 90.08 x 52.56
3.50"	ITLT0350QVRN11CM	TTL	QVGA 320x240 4:3 Normally White, Transmissive	300	24 Bit	60/60/50/55	6 O'Clock	-20~70 -30~80	76.90 x 63.90 x 3.26 90.08 x 52.56
3.50"	ITLT0350QVRF22AM Integrated 4 Wire RTP	TTL	QVGA 320x240 4:3 Normally White, Transmissive	320	24 Bit	60/60/50/55	6 O'Clock	-20~70 -30~80	76.90 x 63.90 x 4.40 70.08 x 52.56
3.50"	ITLT0350VGRF15KM Integrated 4 Wire RTP	TTL	VGA 480x640 3:4 Normally White, Transmissive	420	18 Bit	65/65/50/65	9 O'Clock	-20~70 -30~80	63.00 x 85.00 x 4.10 53.28 x 71.04
3.50"	ITLT0350VGRN14KM	TTL	VGA 480x640 3:4 Normally White, Transmissive	450	18 Bit	65/65/50/65	12 O'Clock	-20~70 -30~80	63.00 x 85.00 x 3.13 53.28 x 71.04
4.30"	ITLT0430WVRN42XL	TTL	WVGA 480x800 16:9 Normally White, Transmissive	230	16 Bit	70/70/55/70	12 O'Clock	-20~70 -30~80	61.46 x 104.25 x 2.10 56.16 x 93.60
4.30"	ITLT0430WQRF26CM Integrated 4 Wire RTP	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	400	24 Bit	70/70/50/70	12 O'Clock	-20~70 -30~80	105.50 x 67.20 x 4.05 95.04 x 53.86
4.30"	ITLT0430WQRF62WM Integrated 4 Wire RTP	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	400	24 Bit	75/75/55/75	6 O'Clock	-20~70 -30~80	105.40 x 67.10 x 3.90 95.04 x 53.85
4.30"	ITLT0430WQRP76ZM Integrated PCAP	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	400	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	105.50 x 67.20 x 4.65 95.04 x 53.86
4.30"	ITLP0430WVRN53SM	TTL	WVGA 480x800 16:9 IPS Normally Black, Transmissive	450	24 Bit	80/80/80/80	Free MVA	-20~70 -30~80	62.66 x 105.95 x 2.2 56.16 x 93.6

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
4.30"	ITLT0430WQRN25CH	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	500	24 Bit	70/70/50/70	12 O'Clock	-20~70 -30~80	105.50 x 67.20 x 2.90 95.04 x 53.86
4.30"	ITLT0430WQRF64ZH Integrated 4 Wire RTP	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	700	24 Bit	75/75/55/75	6 O'Clock	-20~70 -30~80	105.40 x 67.10 x 3.90 95.04 x 53.85
4.30"	ITLT0430WQRN63ZH	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	800	24 Bit	75/75/55/75	6 O'Clock	-20~70 -30~80	105.40 x 67.10 x 2.80 95.04 x 53.86
4.70"	ITLT0470WQRN31AM	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	440	24 Bit	50/55/65/65	6 O'Clock	-20~70 -30~80	114.24 x 72.88 x 3.15 103.68 x 58.75
5.00"	ITLT0500VGRF62ZL_A2 Integrated 4 Wire RTP	TTL	VGA 640x480 4:3 Normally White, Transmissive	200	18 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	117.65 x 88.43 x 10.22 101.60 x 76.18
5.00"	ITLT0500WVRF52WM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	300	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.80 x 76.00 x 4.65 108.00 x 64.80
5.00"	ITLT0500WVRP55WM Integrated PCAP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	300	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.80 x 76.00 x 4.10 108.00 x 64.80
5.00"	ITLT0500WQRN34CM	TTL	WQVGA 480x272 16:9 Normally White, Transmissive	350	18 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.70 x 75.80 x 3.10 110.88 x 62.83
5.00"	ITLT0500WVRN61CM	TTL	WVGA 800x480 16:9 Normally White, Transmissive	350	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.70 x 76.30 x 3.10 108.00 x 64.80
5.00"	ITLT0500WVRF54WH Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	700	18 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.80 x 76.90 x 6.43 108.00 x 64.80
5.00"	ITLT0500WVRN53WH	TTL	WVGA 800x480 16:9 Normally White, Transmissive	800	18 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	120.80 x 76.90 x 4.83 108.00 x 64.80
5.60"	ITLT0560VGRF23CM Integrated 4 Wire RTP	TTL	VGA 640x480 4:3 Normally White, Transmissive	160	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	126.50 x 100.00 x 7.25 112.90 x 84.67
5.60"	ITLT0560VGRF23CM_A1 Integrated 4 Wire RTP	TTL	VGA 640x480 4:3 Normally White, Transmissive	160	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	126.50 x 100.00 x 7.25 112.90 x 84.67
5.70"	ITLT0570VGRN31UM	TTL	VGA 640x480 4:3 Normally White, Transmissive	300	18 Bit	75/75/55/75	6 O'Clock	-20~70 -30~85	127.00 x 98.40 x 8.96 115.20 x 86.40
5.70"	ITLT0570QVRF33ZM Integrated 4 Wire RTP	TTL	QVGA 320x240 4:3 Normally White, Transmissive	400	18 Bit	80/80/70/80	12 O'Clock	-30~85 -30~85	144.00 x 104.60 x 13.80 115.20 x 86.40
5.70"	ITLT0570VGRF33UH Integrated 4 Wire RTP	TTL	VGA 640x480 4:3 Normally White, Transmissive	400	18 Bit	75/75/55/75	6 O'Clock	-20~70 -30~85	127.00 x 98.40 x 10.05 115.20 x 86.40

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
5.70"	ITLT0570QVRN31ZM	TTL	QVGA 320x240 4:3 Normally White, Transmissive	500	18 Bit	80/80/70/70	12 O'Clock	-30~85 -30~85	144.00 x 104.60 x 12.30 115.20 x 86.40
5.70"	ITLT0570VGRF23ZH_A3 Integrated 4 Wire RTP	TTL	VGA 640x480 4:3 Normally White, Transmissive	700	18 Bit	80/80/70/70	12 O'Clock	-30~85 -30~85	144.00 x 104.60 x 13.80 115.20 x 86.40
5.70"	ITLT0570VGRN21AH	TTL	VGA 640x480 4:3 Normally White, Transmissive	700	18 Bit	80/80/70/70	12 O'Clock	-30~85 -30~85	144.00 x 104.60 x 12.30 115.20 x 86.40
5.70"	ITLT0570VGRN33UH	TTL	VGA 640x480 4:3 Normally White, Transmissive	700	18 Bit	75/75/55/75	6 O'Clock	-20~70 -30~85	127.00 x 98.40 x 8.96 115.20 x 86.40
5.70"	ITLT0570QVRN34ZH_A1	TTL	QVGA 240x320 3:4 Normally White, Transmissive	1200	18 Bit	80/80/70/70	12 O'Clock	-30~85 -30~85	144.00 x 104.60 x 12.30 115.20 x 86.40
6.50"	ITLT0650WVLN16CM	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	400	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	155.20 x 89.40 x 8.50 143.40 x 76.70
6.50"	ITLT0650WVRN14CM	TTL	WVGA 800x480 16:9 Normally White, Transmissive	400	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	155.20 x 89.40 x 5.50 143.40 x 76.70
6.50"	ITLT0650VGLF14ZH Integrated 4 Wire RTP	LVDS	VGA 640x480 4:3 Normally White, Transmissive	640	24 Bit	80/80/70/70	6 O'Clock	-30~80 -30~80	153.00 x 118.00 x 12.40 132.50 x 99.40
6.50"	ITLT0650VGLN12AH	LVDS	VGA 640x480 4:3 Normally White, Transmissive	800	24 Bit	80/80/70/70	6 O'Clock	0~50 -20~60	153.00 x 118.00 x 10.90 132.50 x 99.40
7.00"	ITLT0700WVRF22ZL Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	200	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	164.90 x 100.00 x 7.25 154.08 x 85.92
7.00"	ITLT0700SWLN42CM	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	250	24 Bit	75/75/70/75	6 O'Clock	-20~60 -30~70	165.75 x 105.39 x 3.40 153.60 x 90.00
7.00"	ITLT0700SWLP47CM_A3 Integrated PCAP	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	250	24 Bit	85/85/85/85	6 O'Clock	-20~60 -30~70	184.00 x 121.00 x 4.90 153.60 x 90.00
7.00"	ITLT0700WVRN22CL	TTL	WVGA 800x480 16:9 Normally White, Transmissive	250	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	164.90 x 100.00 x 5.70 154.08 x 85.92
7.00"	ITLT0700SWLF43CL Integrated 4 Wire RTP	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	280	24 Bit	75/75/70/75	6 O'Clock	-20~60 -30~70	165.70 x 105.40 x 4.92 153.60 x 90.00
7.00"	ITLT0700WVRF34CL Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	280	18 Bit	70/70/60/70	6 O'Clock	-20~70 -30~80	165.00 x 104.44 x 6.75 152.40 x 91.44
7.00"	ITLT0700WVRP37CM_A2 Advanced PCAP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	280	18 Bit	70/70/60/70	6 O'Clock	-20~60 -30~70	185.40 x 116.80 x 7.00 152.40 x 90.80

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
7.00"	ITLT0700WVRNB1CM	TTL	WVGA 800x480 16:9 Normally White, Transmissive	300	18 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	165.00 x 104.00 x 5.50
7.00"	ITLT0700WVLF26CM Integrated 4 Wire RTP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	320	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 10.25 154.08 x 85.92
7.00"	ITLT0700WVLP68ZM_A4 Integrated PCAP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	320	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.00 x 9.50 152.40 x 91.44
7.00"	ITLT0700WVRF16ZM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	320	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90x 100.00 x 7.25 154.08 x 85.92
7.00"	ITLT0700WVRF24CM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	320	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 7.25 154.08 x 85.92
7.00"	ITLT0700WVLV68ZM Integrated 5 Wire RTP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	350	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	166.50 x 106.18 x 9.54 152.40 x 91.44
7.00"	ITLT0700WVRF61ZM_A1 Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	350	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.00 x 9.54 152.4 x 91.44
7.00"	ITLT0700WVRN32CM_A2	TTL	WVGA 800x480 16:9 Normally White, Transmissive	350	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.44 x 5.20 152.40 x 91.44
7.00"	ITLT0700WVRP38CM_A3 Integrated PCAP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	350	18 Bit	70/70/60/70	6 O'Clock	-20~60 -30~70	185.40 x 116.80 x 7.00 152.40 x 90.80
7.00"	ITLT0700WVRF63ZM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	360	18 Bit	70/70/60/70	6 O'Clock	-30~85 -40~85	165.00 x 104.00 x 9.54 152.40 x 91.44
7.00"	ITLT0700WVLN25CM	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	400	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 8.70 154.08 x 85.92
7.00"	ITLT0700WVLN65ZM	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	400	24 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.00 x 8.00 152.40 x 91.44
7.00"	ITLT0700WVRN24CM	TTL	WVGA 800x480 16:9 Normally White, Transmissive	400	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 5.70 154.08 x 85.92
7.00"	ITLT0700WVRN60ZM_A1	TTL	WVGA 800x480 16:9 Normally White, Transmissive	450	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.00 x 8.00 152.4 x 91.44
7.00"	ITLT0700WVLNC2CM	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	500	24 Bit	70/70/60/60	6 O'Clock	-30~85 -40~95	165.00 x 104.00 x 9.53 152.40 x 91.44
7.00"	ITLT0700WVLP5CH Integrated PCAP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	500	18 Bit	70/70/60/60	6 O'Clock	-30~80 -30~85	184.00 x 121.00 x 11.35 152.40 x 91.44

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
7.00"	ITLT0700WVLP5CH_OB Integrated PCAP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	700	18 Bit	70/70/60/60	6 O'Clock	-30~80 -30~85	184.00 x 121.00 x 11.35 152.40 x 91.44
7.00"	ITLT0700WVLF27ZH Integrated 4 Wire RTP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	800	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 10.25 154.08 x 85.92
7.00"	ITLT0700WVLF67ZH Integrated 4 Wire RTP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	800	24 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.00 x 9.45 152.40 x 91.44
7.00"	ITLT0700WVRP38CH Integrated PCAP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	800	18 Bit	70/70/60/70	6 O'Clock	-20~70 -30~80	185.40 x 116.80 x 8.15 152.40 x 90.80
7.00"	ITLT0700WVLP69ZH Integrated PCAP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	850	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.00 x 9.50 152.40 x 91.44
7.00"	ITLT0700WVLN27ZH	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	1000	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	164.90 x 100.00 x 8.70 154.08 x 85.92
7.00"	ITLT0700WVLN66ZH	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	1000	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.00 x 8.00 152.40 x 91.44
7.00"	ITLT0700WVRN36CH	TTL	WVGA 800x480 16:9 Normally White, Transmissive	1000	18 Bit	70/70/60/70	6 O'Clock	-30~85 -30~85	165.00 x 104.44 x 5.20 152.40 x 91.44
7.00"	ITLT0700WVRN62ZH	TTL	WVGA 800x480 16:9 Normally White, Transmissive	1000	18 Bit	70/70/60/70	6 O'Clock	-30~85 -40~85	165.00 x 104.00 x 8.00 152.40 x 91.44
7.00"	ITLT0700WVRP67ZH	TTL	WVGA 800x480 16:9 Normally White, Transmissive	1000	18 Bit	70/70/60/70	6 O'Clock	-30~80 -40~80	185.40 x 116.80 x 9.50 152.40 x 91.44
7.00"	ITLT0700WVRT20WH Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	1000	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	164.90 x 100.00 x 7.25 154.08 x 85.92
8.00"	ITLT0800SVLN31ZM	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	250	18 Bit	75/75/60/70	6 O'Clock	-20~70 -30~80	183.00 x 141.00 x 8.60 162.00 x 121.50
8.00"	ITLT0800SVRN21ZH	TTL	SVGA 800x600 4:3 Normally White, Transmissive	250	24 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	183.00 x 141.00 x 5.60 162.00 x 121.50
8.00"	ITLT0800WVRF62ZM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	360	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	192.80 x 116.90 x 8.01 176.64 x 99.36
8.00"	ITLT0800WVRF63ZM-A Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	360	24 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	192.80 x 116.90 x 8.01 176.64 x 99.36
8.00"	ITLT0800WVRF73ZM Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	360	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	192.80 x 116.90 x 11.01 176.64 x 99.36

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
8.00"	ITLT0800WVRN72ZM_A1	TTL	WVGA 800x480 16:9 Normally White, Transmissive	450	18 Bit	70/70/50/70	6 O'Clock	-30~85 -30~85	192.80 x 116.90 x 9.40 176.64 x 99.36
8.00"	ITLT0800SVRN22ZH	TTL	SVGA 800x600 4:3 Normally White, Transmissive	500	24 Bit	70/70/50/65	6 O'Clock	-20~70 -30~80	183.00 x 141.00 x 8.60 162.00 x 121.50
8.40"	ITLT0840SVLF46GM_A5 Integrated 4 Wire RTP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	350	18 Bit	75/75/60/70	6 O'Clock	-20~70 -30~85	189.75 x 149.40 x 9.55 170.40 x 127.80
8.40"	ITLT0840SVLV47ZM Integrated 5 Wire RTP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	350	18 Bit	75/75/60/70	6 O'Clock	-20~70 -30~85	189.75 x 149.40 x 10.20 170.40 x 127.80
8.40"	ITLT0840SVLN45GM	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	400	18 Bit	75/75/60/70	6 O'Clock	-20~70 -30~85	189.75 x 149.40 x 8.00 170.40 x 127.80
8.40"	ITLT0840SVLF56GH Integrated 4 Wire RTP	TTL	SVGA 800x600 4:3 Normally White, Transmissive	800	18 Bit	75/75/60/70	6 O'Clock	-20~70 -30~85	189.75 x 149.40 x 9.55 170.40 x 127.80
8.40"	ITLT0840SVLN53TH	TTL	SVGA 800x600 4:3 Normally White, Transmissive	1000	18 Bit	75/75/60/70	6 O'Clock	-20~ 70 -30 ~ 80	203.00 x 142.50 x 5.70 170.40 x 127.80
8.40"	ITLT0840SVLV57GH Integrated 5 Wire RTP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	1000	18 Bit	75/75/60/70	6 O'Clock	-20~70 -30~80	203.00 x 142.50 x 8.05 170.40 x 127.80
9.00"	ITLT0900WVRN22HM	TTL	WVGA 800x480 16:9 Normally White, Transmissive	250	18 Bit	70/70/50/70	6 O'Clock	-20~70 -30~80	211.10 x 126.50 x 5.90 198.00 x 111.70
9.00"	ITLT0900WXLN42HM	LVDS	WXGA 1280x800 16:10 Normally White, Transmissive	250	24 Bit	70/70/70/50	6 O'Clock	-10~60 -20~70	206.76 x 135.06 x 3.60 193.90 x 121.20
9.70"	ITLP0970XGLF14CM_A1 Integrated 4 Wire RTP	LVDS	XGA 1024x768 4:3 IPS Normally Black, Transmissive	300	18 Bit	89/89/89/89	Free IPS	-20~70 -25~70	211.10 x 165.00 x 7.35 197.00 x 147.00
9.70"	ITLP0970XGLP17CM Integrated PCAP	LVDS	XGA 1024x768 4:3 IPS Normally Black, Transmissive	300	18 Bit	89/89/89/89	6 O'Clock	-25~70 -25~70	211.10 x 165.00 x 7.35 197.00 x 147.00
9.70"	ITLP0970XGLN13VM	LVDS	XGA 1024x768 4:3 IPS Normally Black, Transmissive	350	18 Bit	89/89/89/89	6 O'Clock	-20~70 -25~70	210.20 x 164.00 x 5.45 197.00 x 147.00
9.70"	ITLP0970XGLN12CM_A7	LVDS	XGA 1024x768 4:3 MVA Normally Black, Transmissive	420	18 Bit	89/89/89/89	Free MVA	-20~70 -25~70	210.20 x 164.00 x 5.45 197.00 x 147.00
9.70"	ITLP0970XGLP25CH Integrated PCAP	LVDS	XGA 1024x768 4:3 IPS Normally Black, Transmissive	510	18 Bit	89/89/89/89	Free IPS	-20~70 -25~70	236.70 x 183.60 x 6.15 196.61 x 147.45
10.10"	ITLT1010WXLP47ZL Integrated PCAP	LVDS	WXGA 1280x800 16:9 Normally White, Transmissive	200	24 Bit	75/75/75/70	6 O'Clock	20~60 30~70	249.56 x 168.20 x 5.40 217.00 x 136.00

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
10.10'	ITLP1010WXL12CM Integrated 4 Wire RTP	LVDS	WXGA 1280x800 16:9 MVA Normally Black, Transmissive	350	24 Bit	85/85/85/85	Free MVA	-20~60 -30~70	229.46 x 149.10 x 4.25 216.96 x 135.60
10.10'	ITLP1010WXL13CM	LVDS	WXGA 1280x800 16:9 IPS Normally Black, Transmissive	350	24 Bit	85/85/85/85	Free IPS	-20~60 -30~70	229.46 x 149.10 x 2.50 216.96 x 135.60
10.10'	ITLT1010SWLN21VM	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	500	18 Bit	80/80/70/80	6 O'Clock	-30~85 -30~85	244.00 x 143.00 x 12.40 222.70 x 125.28
10.10'	ITLT1010SWLN24VH	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	800	18 Bit	80/80/70/80	6 O'Clock	-30~85 -30~85	244.00 x 143.00 x 12.40 222.70 x 125.28
10.20'	ITLT1020WVLF47ZM Integrated 4 Wire RTP	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	280	24 Bit	65/65/45/65	6 O'Clock	-30~85 -30~85	235.00 x 145.80 x 10.90 222.00 x 132.48
10.20'	ITLT1020WVRF45ZM_A4 Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9	280	24 Bit	65/65/45/65	6 O'Clock	-20~70 -30~80	235.00 x 145.80 x 11.90 222.00x 132.48
10.20'	ITLT1020SWLF22PM Integrated 4 Wire RTP	LVDS	XGA 1024x600 16:9 Normally White, Transmissive	320	18 Bit	70/70/65/55	6 O'Clock	-20~70 -30~80	235.00 x 145.80 x 7.55 222.72 x 130.50
10.20'	ITLT1020WVLN46ZM	LVDS	WVGA 800x480 16:9 Normally White, Transmissive	350	24 Bit	65/65/45/65	6 O'Clock	-30~85 -30~85	235.00 x 145.80 x 9.40 222.00 x 132.48
10.20'	ITLT1020SWLN21PM	LVDS	WSVGA 1024x600 16:9 Normally White, Transmissive	400	18 Bit	70/70/65/55	6 O'Clock	-20~70 -30~80	235.00 x 145.80 x 5.30 222.72 x 130.50
10.20'	ITLT1020WVRF43ZH Integrated 4 Wire RTP	TTL	WVGA 800x480 16:9 Normally White, Transmissive	800	18 Bit	65/65/45/65	6 O'Clock	-30~85 -30~85	235.00 x 145.80 x 11.9 222.00 x 132.48
10.40'	ITLT1040SVRF16ZL Integrated 4 Wire RTP	TTL	SVGA 800x600 4:3 Normally White, Transmissive	220	24 Bit	70/70/50/60	6 O'Clock	-20~70 -20~80	228.40 x 175.40x 7.45 211.20 x 158.40
10.40'	ITLT1040SVLN23ZL	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	250	18 Bit	75/75/50/60	6 O'Clock	-10~60 -20~70	228.40 x 175.40 x 10.80 211.20 x 158.40
10.40'	ITLT1040SVRN13ZL	TTL	SVGA 800x600 4:3 Normally White, Transmissive	250	24 Bit	70/70/50/60	6 O'Clock	-10~60 -20~70	228.40 x 175.40 x 5.90 211.20 x 158.40
10.40'	ITLT1040XGLF45TM_A2 Integrated 4 Wire RTP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	300	18 Bit	70/70/65/55	6 O'Clock	-20~70 -30~80	236.00 x 174.30 x 9.00 211.20 x 158.40
10.40'	ITLT1040SVLF33TM Integrated 4 Wire RTP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	320	18 Bit	65/65/45/65	6 O'Clock	-20~70 -30~80	236.00 x 176.90 x 7.20 211.20 x 158.40
10.40'	ITLT1040SVLV34TM Integrated 5 Wire RTP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	320	18 Bit	65/65/45/65	6 O'Clock	-20~70 -30~80	236.00 x 176.90 x 7.80 211.20 x 158.40

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
10.40"	ITLT1040XGLP47TM_A1 Integrated PCAP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	320	18 Bit	70/70/65/55	6 O'Clock	-20~70 -30~80	239.10 x 186.30 x 9.77 211.20 x 158.40
10.40"	ITLT1040SVLN26ZM	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	350	18 Bit	75/75/50/60	6 O'Clock	-10~60 -20~70	228.40 x 175.40 x 10.80 211.20 x 158.40
10.40"	ITLV1040XGLP46AM Integrated PCAP	LVDS	XGA 1024x768 4:3 MVA Normally Black, Transmissive	360	24 Bit	88/88/88/88	Free MVA	-30~80 -30~80	259.10 x 206.30 x 9.40 210.40 x 157.80
10.40"	ITLV1040XGLV44AM Integrated 5 Wire RTP	LVDS	XGA 1024x768 4:3 MVA Normally Black, Transmissive	360	24 Bit	88/88/88/88	Free MVA	-30~80 -30~80	238.60 x 175.80 x 8.85 210.40 x 157.80
10.40"	ITLT1040SVLN31TM	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	400	18 Bit	65/65/45/65	6 O'Clock	-20~70 -30~80	236.00 x 176.90 x 5.60 211.20 x 158.40
10.40"	ITLT1040SVLN41AM	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	400	24 Bit	80/80/60/80	6 O'Clock	-30~85 -30~85	243.00 x 184.00 x 8.00 211.20 x 158.40
10.40"	ITLT1040VGRF24CM Integrated 4 Wire RTP	TTL	VGA 640x480 4:3 Normally Black, Transmissive	400	18 Bit	88/88/88/88	Free MVA	-30~80 -30~80	225.50 x 176.30 x 10.89 211.20 x 158.40
10.40"	ITLV1040XGLN42AM	LVDS	XGA 1024x768 4:3 MVA Normally Black, Transmissive	450	24 Bit	88/88/88/88	Free MVA	-30~80 -30~80	238.60 x 175.80 x 6.50 210.40 x 157.80
10.40"	ITLT1040VGRN22CM	TTL	VGA 640x480 4:3 Normally Black, Transmissive	500	18 Bit	88/88/88/88	Free MVA	-30~80 -30~80	225.50 x 176.30 x 7.81 211.20 x 158.40
10.40"	ITLV1040XGLN53TM	LVDS	XGA 1024x768 4:3 Normally Black, Transmissive	500	24 Bit	88/88/88/88	Free IPS	-30~70 -30~80	225.50 x 176.30 x 8.70 210.40 x 157.80
10.40"	ITLT1040SVRN15ZH	TTL	SVGA 800x600 4:3 Normally White, Transmissive	650	24 Bit	70/70/50/60	6 O'Clock	-10~60 -20~70	228.40 x 175.40 x 8.90 211.20 x 158.40
10.40"	ITLT1040SVLF37ZH Integrated 4 Wire RTP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	800	18 Bit	65/65/45/65	6 O'Clock	-20~70 -30~80	236.00 x 176.90 x 7.20 211.20 x 158.40
10.40"	ITLT1040SVLN32GH	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	1000	18 Bit	65/65/45/65	6 O'Clock	-20~70 -30~80	236.00 x 176.90 x 5.60 211.20 x 158.40
10.40"	ITLT1040SVLN35TM	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	1000	18 Bit	65/65/45/65	6 O'Clock	-20~70 -30~80	236.00 x 176.90 x 5.60 211.20 x 158.40
10.40"	ITLT1040VGLN24CH	LVDS	VGA 640x480 4:3 Normally White, Transmissive	1000	24 Bit	80/80/60/80	6 O'Clock	-30~ 85 -30~ 85	243.00 x 176.60 x 8.00 211.20 x 158.40
10.40"	ITLT1040XGLP48TH Integrated PCAP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1000	18 Bit	70/70/65/55	6 O'Clock	-30~80 -30~80	259.10 x 206.30 x 10.10 211.20 x 158.40

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
12.10'	ITLT1210SVLP44ZL Integrated PCAP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	250	24 Bit	80/80/75/65	6 O'Clock	-30~80 -30~80	289.47 x 222.00 x 11.85 246.00 x 184.50
12.10'	ITLT1210SVLF45ZL Integrated 4 Wire RTP	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	360	24 Bit	80/80/75/65	6 O'Clock	-30~80 -30~80	279.00 x 209.00 x 10.55 246.00 x 184.50
12.10'	ITLT1210WXLN42CM	LVDS	WXGA 1280x800 16:9 Normally Black, Transmissive	400	24 Bit	85/85/85/85	6 O'Clock	-10~70 -20~80	278.00 x 184.00 x 8.16 261.12 x 163.20
12.10'	ITLT1210XGLV17ZM Integrated 5 Wire RTP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	400	24 Bit	80/80/60/80	6 O'Clock	-30~85 -30~85	279.00 x 209.00 x 9.00 245.76 x 184.32
12.10'	ITLT1210SVLN42ZM	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	450	24 Bit	80/80/75/65	6 O'Clock	-30~85 -30~85	279.00 x 209.00 x 9.00 246.00 x 184.50
12.10'	ITLT1210XGLN13AM	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	500	24 Bit	80/80/60/80	6 O'Clock	-30~80 -30~80	279.00 x 209.00 x 9.00 245.76 x 184.32
12.10'	ITLT1210SVLN51ZH	LVDS	SVGA 800x600 4:3 Normally White, Transmissive	1000	24 Bit	80/80/75/65	6 O'Clock	-30~80 -30~80	279.00 x 209.00 x 9.00 246.00 x 184.50
12.10'	ITLT1210XGLN17GH	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1000	24 Bit	80/80/70/70	6 O'Clock	-30~80 -30~80	279.00 x 209.00 x 9.00 245.76 x 184.32
12.10'	ITLT1210XGLN34ZH	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1000	24 Bit	80/80/70/70	6 O'Clock	-30~80 -30~80	280.00 x 210.00 x 12.00 245.76 x 184.32
15.00'	ITLT1500XGLP16CL Integrated PCAP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	200	24 Bit	80/80/70/70	6 O'Clock	-30~80 -30~80	339.10 x 262.15 x 14.60 303.00 x 228.00
15.00'	ITLT1500XGLV15CL Integrated 5 Wire RTP	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	200	24 Bit	80/80/70/70	6 O'Clock	-30~80 -30~80	339.10 x 262.15 x 14.20 303.00 x 228.00
15.00'	ITLT1500XGLN12CL	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	250	24 Bit	80/80/70/70	6 O'Clock	-30~80 -40~85	326.50 x 235.30 x 11.80 304.10 x 228.10
15.00'	ITLT1500XGLN43WH	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1000	24 Bit	80/80/70/70	6 O'Clock	-30~80 -40~85	326.50 x 235.30 x 11.80 304.10 x 228.10
15.00'	ITLT1500XGLN54GE_AR	LVDS	XGA 1024x768 4:3 Normally White, Transmissive	1800	24 Bit	80/80/60/80	6 O'Clock	-30~85 -30~85	326.50 x 253.50 x 13.10 304.10 x 228.10
15.60'	ITLT1560WXLN31AL	LVDS	XGA 1366x768 16:9 Normally White, Transmissive	300	24 Bit	85/85/80/80	6 O'Clock	-10~50 -20~60	363.80 x 215.90 x 16.85 344.20 x 193.50
15.60'	ITLT1560WXLN32AM	LVDS	XGA 1366x768 16:9 Normally White, Transmissive	420	24 Bit	85/85/80/80	6 O'Clock	-10~50 -20~60	363.80 x 215.90 x 16.85 344.20 x 193.50

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
17.00'	ITLT1700SXLN32ZH	LVDS	XGA 1280x1024 5:4 Normally White, Transmissive	600	24 Bit	85/85/80/80	6 O'Clock	-30~85 -30~85	358.50 x 296.50 x 18.00 337.92 x 270.34
17.00'	ITLT1700SXLN44GH	LVDS	XGA 1280x1024 5:4 Normally White, Transmissive	1000	24 Bit	85/85/80/80	6 O'Clock	-20~60 -20~70	358.50 x 296.50 x 15.80 337.92 x 270.34
17.00'	ITLT1700SXLN44GH_A2	LVDS	XGA 1280x1024 5:4 Normally White, Transmissive	1000	24 Bit	85/85/80/80	6 O'Clock	-20~60 -20~70	358.50 x 296.50 x 15.80 337.92 x 270.34
17.00'	ITLT1700SXLP36GH Integrated PCAP	LVDS	SXGA 1280x1024 5:4 Normally White, Transmissive	1000	24 Bit	85/85/80/80	6 O'Clock	-30~85 -30~85	379.92 x 312.34 x 22.10 337.92 x 270.34
18.50'	ITLT1850HDLP23GM Integrated PCAP	LVDS	WXGA 1366x768 16:9 Normally White, Transmissive	240	24 Bit	85/85/80/80	6 O'Clock	-20~60 -20~50	445.00 x 265.60 x 19.22 409.80 x 230.40
18.50'	ITLT1850HDLN21GM	LVDS	WXGA 1366x768 16:9 Normally White, Transmissive	300	24 Bit	85/85/80/80	6 O'Clock	-20~50 -20~60	430.40 x 254.60 x 16.40 409.80 x 230.40
18.50'	ITLT1850HDLN13GH	LVDS	WXGA 1366x768 16:9 Normally White, Transmissive	650	24 Bit	85/85/80/80	6 O'Clock	-20~50 -20~60	430.40 x 254.60 x 10.50 409.80 x 230.40
18.50'	ITLT1850HDLP25GH Integrated PCAP	LVDS	WXGA 1366x768 16:9 Normally White, Transmissive	800	24 Bit	85/85/80/80	6 O'Clock	-20~60 -20~50	445.00 x 265.60 x 19.22 409.80 x 230.40
19.00'	ITLT1900WXLN11CL	LVDS	WXGA+ 1440x900 16:9 Normally White, Transmissive	250	24 Bit	85/85/80/80	6 O'Clock	-0~50 -20~60	428.00 x 278.00 x 10.50 408.24 x 255.15
19.00'	ITLT1900SXLN42ZM Integrated 5 Wire RTP	LVDS	SXGA 1280x1024 5:4 Normally White, Transmissive	280	24 Bit	85/85/80/80	6 O'Clock	-0~50 -20~60	396.00 x 324.00 x 20.15 376.30 x 301.10
19.00'	ITLT1900SXLN41AM	LVDS	SXGA 1280x1024 5:4 Normally White, Transmissive	350	24 Bit	88/88/85/85	6 O'Clock	-0~50 -20~60	396.00 x 324.00 x 17.80 376.30 x 301.10
19.00'	ITLT1900SXLN51AM	LVDS	XGA 1280x1024 5:4 Normally White, Transmissive	350	24 Bit	85/85/80/80	6 O'Clock	-30~85 -30~85	396.00 x 324.00 x 15.18 376.30 x 301.10
19.00'	ITLT1900SXLN43GH	LVDS	SXGA 1280x1024 5:4 Normally White, Transmissive	550	24 Bit	88/88/85/85	6 O'Clock	-0~50 -20~60	396.00 x 324.00 x 17.80 376.30 x 301.10
19.00'	ITLT1900SXLN44BE	LVDS	XGA 1280x1024 5:4 Normally White, Transmissive	1200	24 Bit	88/88/80/85	6 O'Clock	-20~70 -30~80	396.00 x 324.00 x 17.80 376.30 x 301.10
21.50'	ITLV2150HDLN12AM	LVDS	HD 1920x1080 16:9 MVA Normally Black, Transmissive	300	24 Bit	89/89/89/89	Free IPS	-20~60 -20~60	495.60 x 292.20 x 17.35 476.64 x 268.11
21.50'	ITLV2150HDLN22BH	LVDS	Full HD 1920 x 1080 MVA Normally Black, Transmissive	1200	24 Bit	89/89/89/89	Free MVA	-20~70 -30~70	495.60 x 292.20 x 17.35 476.64 x 268.11



In Touch Electronics Product Offering

Size	Product ID	I/F	Display Resolution Display Mode	Nits	Color Depth	View Angle	View Direction	Op Temp St Temp	Outer Dimensions (mm) Active Area (mm)
21.50'	ITLV2150HDLN33BH	LVDS	HD 1920x1080 Normally Black, Transmissive	1200	24 Bit	89/89/89/89	Free MVA	-20~70 -30~70	495.60 x 292.20 x 10.50 476.64 x 268.11